

Auto Body Supply, Inc.



PPG Industries took a starring role at the 19th annual Goodguys PPG Nationals held July 8–10 at the Ohio Expo Center in Columbus. The annual PPG Dream Car award winners were named, and a PPG-painted car took Street Rod of the Year honors. In addition, PPG's DITZLER® DSC5250 Satin Clear Kit won the inaugural Best New Product award in the extremely competitive Paint & Car Care Products category.

The PPG Dream Car awards are given to the two cars or trucks that best exemplify the outstanding use of color, design, gloss and execution in a paint job. The popular accolade is highly prized with competition always stiff, as custom car painters and builders work hard to stand out from the crowd. This year, two exceptional cars earned that distinction: a 1929 Ford Model A owned by Dale Spangenberg III of Willoughby, Ohio, and a 1971 Oldsmobile 442 owned by Ed Pienta of Wilkes-Barre, PA.

The Street Rod of the Year award went to a 1939 Oldsmobile, "Olds Cool," painted by Charley Hutton and owned by Billy and Debbie Thomas of Corpus Christi, Texas. The Street Rod competition is open to all cars through the 1949 model year. Hutton gave Olds Cool a standout finish.



SEPTEMBER NEWSLETTER 2016

2034 O Street
Lincoln, NE 68510
402-477-3941

abodysupply2@neb.rr.com

www.autobodylincoln.com

U-POL RAPTOR Protective Coating

Now available in a 1 liter kit



The new 1 Liter size is perfect for repairs, touch ups, and small projects. A 1 Liter kit covers 30 sq. ft. Available in black or tint-able.

WAX & GREASE REMOVERS are products that are used most of the time without any thought of their use. Typically they are sprayed on and wiped off, PPG has formulated several different products for different uses. Below are some tips for the proper use of wax & grease removers.

- Clean an area no larger than 2' X 2' to avoid premature drying
- Apply a generous amount of cleaner with a clean white cloth or a hand held spray bottle
- Initial application floats contaminants to the surface. Wipe with a clean dry cloth to remove the contaminants
- For maximum results, wipe dry with a clean white cloth in one direction only while the surface is still wet to eliminate smearing of contaminants